Certificate Number Report Reference Date	^{LL} UL-US-2237729-0 ^{JJ} ^{LL} E364473-20220922 ^{JJ} 26-Sep-2022
Issued to:	AOK LED Light Company Limited East Suite, 3/F, Building 1, St George's Science & Technology Industrial Park. (2/F, Plant 4, St George's Science & Technology Industrial Park). North Xinyu Rd, Xinqiao St. Shenzhen, Guangdong 518125 China
This is to certify that representative samples of	IFAM - Light-emitting-diode Surface-mounted Luminaires See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 1598, 5th Ed., Issue Date: 2021-03-26, Revision Date: 2021-06-18
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bample

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date ^{LL}UL-US-2237729-0^{JJ} ^{LL}E364473-20220922^{JJ} 26-Sep-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
AOK-115WPLA-HVS-XX-XX-XXXX-XX, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-115WPLA-NVS-XX-XX-XX-XX-XX, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-150WPLA-HVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-150WPLA-NVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-180WPLA-HVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol	LED Surface Mounted Luminaire

Bruce Mahrenholz, Director North American Certification Program

3

UL LLC

R

Certificate Number Report Reference Date ^{LL}UL-US-2237729-0^{JJ} ^{LL}E364473-20220922^{JJ} 26-Sep-2022

provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	
AOK-180WPLA-NVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-200WPLA-HVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-200WPLA-NVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-230WPLA-HVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-230WPLA-NVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the	LED Surface Mounted Luminaire

Bruce Mahrenholz, Director North American Certification Program

UL LLC

R

Certificate Number Report Reference Date ^{LL}UL-US-2237729-0^{JJ} ^{LL}E364473-20220922^{JJ} 26-Sep-2022

third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	\mathbf{u}
AOK-75WPLA-HVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-75WPLA-NVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire

Bamely



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date	^{LL} UL-CA-2236483-0 ^{JJ} ^{LL} E364473-20220922 ^{JJ} 26-Sep-2022
Issued to:	AOK LED Light Company Limited East Suite, 3/F, Building 1, St George's Science & Technology Industrial Park. (2/F, Plant 4, St George's Science & Technology Industrial Park). North Xinyu Rd, Xinqiao St. Shenzhen, Guangdong 518125 China
This is to certify that representative samples of	IFAM7 - Light-emitting-diode Surface-mounted Luminaires Certified for Canada See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	CSA C22.2 NO. 250.0:21, 5th Ed., Issue Date: 2021-03-26, Revision Date: 2021-06-18
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bamely

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Certificate Number Report Reference Date ^{LL}UL-CA-2236483-0^{JJ} ^{LL}E364473-20220922^{JJ} 26-Sep-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
AOK-115WPLA-HVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-115WPLA-NVS-XX-XX-XX-XX-XX, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-150WPLA-HVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-150WPLA-NVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-180WPLA-HVS-XX-XX-XXXXX-XX, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol	LED Surface Mounted Luminaire

Bruce Mahrenholz, Director North American Certification Program

3

UL LLC

R

Certificate Number L Report Reference L Date 2

^{LL}UL-CA-2236483-0^{JJ} ^{LL}E364473-20220922^{JJ} 26-Sep-2022

LED Surface Mounted Luminaire
LED Surface Mounted Luminaire

Bruce Mahrenholz, Director North American Certification Program

UL LLC

R

Certificate Number Report Reference Date

^{LL}UL-CA-2236483-0^{JJ} ^{LL}E364473-20220922^{JJ} 26-Sep-2022

third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	$\mathbf{L}(\mathbf{U}_{1})(\mathbf{U}_{1})(\mathbf{U}_{2})$
AOK-75WPLA-HVS-XX-XX-XXXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire
AOK-75WPLA-NVS-XX-XX-XXX-XX-X, where the first XX can be any letters for brand of LED, the second XX represents Motion Sensor can be 00 – No sensor provided, PIR= PIR sensor, or PH – Photocontrol provided, the XXXX can be any letters for Color Temperature of LED and Color Rendering Index, the third XX can be any letters for beam angles, the X can be A, B, C, D, E, F, G represents Mounting Bracket.	LED Surface Mounted Luminaire

Bamely



Bruce Mahrenholz, Director North American Certification Program

UL LLC